

● YOUR
● SMART
● ENERGY



SMILE-G3

RESIDENTIAL SERIES

POWER

3.68 / 5 kW

CAPACITY

10.1 kWh Battery Modular
Expandable To 60.5 kWh



200% PV Input

Grid-Forming Function

Off-Grid Parallel Operation

Faster Response for VPP Control



SMILE-G3



Model	SMILE-G3-S3.6	SMILE-G3-S5	SMILE-G3-B5
System Specification			
Nominal Output Power	3680 W	5000 W	5000 W
Capacity Range	10.1 ~ 60.5 kWh (95% DoD)		
Battery Chemistry	LFP (LiFePO4)		
IP Protection	IP65 (Outdoor)		
System Dimension (W x D x H)	610 x 250 x 1161 mm (with Bracket)		
System Weight	109.5 kg		
Warranty	5 Year Product Warranty, 10 Year Battery Performance Warranty		

Inverter Technical Specification			
Model	SMILE-G3-S3.6-INV	SMILE-G3-S5-INV	SMILE-G3-B5-INV
Coupling	Hybrid	Hybrid	AC
Max. PV Input Power	7360 W	10000 W	NA
Max. PV Input Current	15 A / 15 A		NA
Max. PV Input Voltage	580 V		NA
MPPT Number/Max. Input Strings Number Per MPPT	2/1		NA
MPPT Voltage Range	100 ~ 550 V		NA
Max. PV Short-circuit Current	18.75 A / 18.75 A		NA
Max. Charging/Discharging Current	60 A		
Max. Charging/Discharging Power	3680 W	5000 W	5000 W
Rated Frequency	50 / 60 Hz		
Rated Voltage	230 V		
Rated Output Apparent Power (Grid Port)	3680 VA	5000 VA	5000 VA
Rated Output Apparent Power (Backup Port)	3680 VA	5000 VA	5000 VA
Max. AC input Power (Grid Port)	7360 W	10000 W	10000 W
Rated Output Current (Grid Port)	16 A	21.7 A	21.7 A
Max. AC Output Current (Grid Port)	16 A	21.7 A	21.7 A
Rated Output Current (Backup Port)	16 A	21.7 A	21.7 A
Max. AC Output Current (Backup Port)	16 A	21.7 A	21.7 A
Max Inverter Efficiency	97.3%		
Backup	UPS		
Communication	Ethernet / WiFi		
Humidity	0~90% (No Condensing)		
Dimension (W x D x H)	610 x 212 x 366 mm		
Weight	19.5 kg		
Safety	IEC 62109, IEC 62040		
EMC	EN61000-6-1/-2 /-3/-4		
Grid Regulation	AS4777.2, NRS 097, VDE 0126, VDE 4105, EN 50549		

Battery Technical Specification	
Module Mode	SMILE-G3-BAT-10.1P
Module Capacity	10.1 kWh
Usable Capacity	9.6 kWh
Depth of Discharge (DoD)	95%
Nominal Voltage	96 V
Battery Voltage Range	91.5 V ~ 106.5 V
Max. Charging/Discharging Current	60 A
Operating Temperature Range	-10 °C ~ 50 °C*
Cycle Life	8000**
Battery Modules Connection	1 ~ 6 in Parallel

* When the ambient temperature is too low or too high, the performance of battery may be limited.
 ** Under specific test conditions.



Alpha ESS Co., Ltd.

+86 513 8060 6891
 info@alpha-ess.com
 www.alphaess.com
 Jinhua Road 888, Nantong High-Tech Industrial Development Zone, Nantong, Jiangsu Province, China

Alpha ESS Suzhou Co., Ltd.

+86 512 6828 7609
 info@alpha-ess.com
 www.alphaess.com
 Building 10-A, Canal Town Industrial Park, 99 Taihu E Rd, Wuzhong District, Suzhou, Jiangsu Province, China

Alpha ESS Europe GmbH

+49 610 3459 1601
 europe@alpha-ess.de
 www.alphaess.de
 Paul-Ehrlich-Straße 1a, Langen, Hessen D-63225 Germany

Alpha ESS Australia Pty. Ltd.

+61 02 9000 7676
 Australia@alpha-ess.com
 www.alphaess.com
 8/15-21 Gibbes Street, Chatswood, NSW 2067 Australia

Alpha ESS Italy S.r.l.

+39 339 462 4288
 info@alpha-ess.it
 www.alphaess.com
 Via Don Minzoni, 17, Calenzano Firenze 50041 Italy

Alpha ESS UK Ltd.

+44 145 354 5222
 info@alpha-ess.com
 Drake house, Long street, Dursley, gl11 4hh UK

Alpha ESS International Pte. Ltd.

+65 6513 1125 / +65 6513 1126
 Singapore@alpha-ess.com
 2 Corporation Road #01-06A Corporation Place 618494 Singapore

Alpha ESS USA, Inc.

+1 408 368 7828
 usa@alpha-ess.com
 Unit 5 2180 S Ivanhoe St, Denver, CO 80222 USA

Alpha ESS Korea Co., Ltd.

info@alpha-ess.com
 2F, 19-4, Nohyeong 11-gil, Jeju-si, Jeju-do, Republic of Korea